
PREVIEW ENGINE
104
150
102
108
110
160
CCD MODULE
CCD CONTROLLER
BURST MODE COMPRESSION
SDRAM CONTROLLER
SDRAM
NTSC/PAL ENCODER
TV
DSP
122
128
106
130
IMAGE BUFFERS
ARM
MEMORY
124
126
120
USB CORE
142
IMaging EXtension (iMX)
VLC
100
132
I/O BLOCK
140
DSP SUBSYSTEM

FIG. 1a


PREVIEW ENGINE
CCD MODULE
CCD CONTROLLER
BURST MODE COMPRESSION
SDRAM CONTROLLER
SDRAM
TV
NTSC/PAL ENCODER
DSP
DSP SUBSYSTEM
IMAGE BUFFERS
ARM
MEMORY
USB CORE
I/O BLOCK
IMaging EXtension (iMX)
VLC

FIG. 2


SDRAM
160
COMPOSITE/ R/G/B OUTPUT
DAC (x4)
NTSC/PAL ENCODER
106
ENCODER I/F
OSD
105
CCD TC
EXTERNAL CPU
140
142
USB Xciever
USB (WITH RAM)
UART
GIO
UART
TIMER (x4)
WDT
IrDA (WITH RAM)
SERIAL I/F
SDRAM DATA BUS
DMA BUS
SDRAM CONTROLLER 110
DMA
162
134
BUS CONTROLLER
ARM71TDMIE
32K BYTES RAM
130
132
JTAG I/F
170
JTAG
INTERRUPT CONTROLLER
CLOCK CONTROLLER (WITH DPLL)
CFC/ SSF
FLASH MEMORY/ CFC/SSF
182
PREVIEW ENGINE (WITH RAM)
104
BURST MODE COMPRESSION/ DE-COMPRESSION
108
EM I/F
TEST CONTROLLER
ARM BUS
HPIB
136
DSP CONTROLLER
DSP 122
32K WORD RAM
123
IMAGE BUFFERS (WITH RAM)
128
126
VLC ENGINE
CCD CONTROLLER
102
IMAGING EXTENSION
124
CCD MODULE
150
A/D D/A
SERIAL I/F FOR AUDIO

FIG. 1b

Docket: TI-28764



FIG. 1c

Docket: TI-28764


PREVIEW ENGINE
CCD MODULE
CCD CONTROLLER
BURST MODE COMPRESSION
SDRAM CONTROLLER
SDRAM
DSP
DSP SUBSYSTEM
NTSC/PAL ENCODER
TV
IMAGE BUFFERS
ARM
MEMORY
USB CORE
I/O BLOCK
IMaging EXtension (iMX)
VLC

FIG. 3a


47.8 cyc/pxl=
12230 cyc/16x16 pxl
SDRAMC
DSP
iMX
VLC
A→A
B→B
iMX USES BUFFER A
VLC, SDRAMC,
DSP USE BUFFER B
iMX USES BUFFER B
VLC, SDRAMC,
DSP USE BUFFER A

FIG. 3b


PREVIEW ENGINE
SDRAM
CCD MODULE
CCD CONTROLLER
BURST MODE ENGINE
SDRAM CONTROLLER
NTSC/PAL ENCODER
TV
DSP SUBSYSTEM
DSP
DMA
CFC
IMAGE BUFFERS
ARM
MEMORY
USB CORE
I/O BLOCK
IMaging EXtension (iMX)
VLC

FIG. 4


PREVIEW ENGINE
CCD MODULE
CCD CONTROLLER
BURST MODE COMPRESSION
SDRAM
SDRAM CONTROLLER
NTSC/PAL ENCODER
TV
DSP
DSP SUBSYSTEM
IMAGE BUFFERS
ARM
MEMORY
USB CORE
I/O BLOCK
IMaging EXtension (iMX)
VLC

FIG. 5



FIG. 6

R	G	R	G
G	B	G	B
R	G	R	G
G	B	G	B

FIG. 7a

Ye	Cy	Ye	Cy
G	Mg	G	Mg
Ye	Cy	Ye	Cy
G	Mg	G	Mg

FIG. 7b



FIG. 8



FIG. 9a



FIG. 9b



FIG. 9c



FIG. 10a



FIG. 10b



FIG. 10c



FIG. 10d


OUTPUT OF HORIZONTAL INTERPOLATION
VERTICAL INTERPOLATION
$b_{12}=\frac{b_{02}+b_{22}}{2}$
SIMPLE MODE
COLOR ADJUSTMENT (NORMAL MODE)
$\overline{b_{12}}=\frac{b_{02}-G_{02}+b_{22}-G_{22}}{2}-g_{12}$

FIG. 10e


OUTPUT OF HORIZONTAL INTERPOLATION
VERTICAL INTERPOLATION
$ye_{11}=\frac{ye_{01}+ye_{21}}{2}$
$cy_{11}=\frac{Cy_{01}+Cy_{21}}{2}$
SIMPLE MODE
COLOR ADJUSTMENT (NORMAL MODE)
$a=g_{11}+Mg_{11}-ye_{11}-cy_{11}$
$\overline{ye_{11}}=ye_{11}+\frac{a}{4}$
$\overline{cy_{11}}=cy_{11}+\frac{a}{4}$
$\overline{g_{11}}=g_{11}-\frac{a}{4}$
$\overline{mg_{11}}=Mg_{11}-\frac{a}{4}$

FIG. 10f



NOISE FILTER = OFF

$$\begin{cases} L_121 = R_{12} \\ R_121 = g_{12} \\ L_101 = \dfrac{G_{02}+G_{22}}{2} \\ R_101 = \dfrac{b_{02}+b_{22}}{2} \end{cases}$$

NOISE FILTER = ON

$$\begin{cases} L_121 = R_{12} - g_{12} + \dfrac{G_{02}+2g_{12}+G_{22}}{4} \\ R_121 = \dfrac{G_{02}+2g_{12}+G_{22}}{4} \\ L_101 = \dfrac{G_{02}+G_{22}}{2} \\ R_101 = \dfrac{b_{02}+b_{22}}{2} \end{cases}$$

FIG. 10g


L_original[7..0]
8 BITS
Z-1
Z-1
8 bits
9 BITS
x 1/2
L_101[7..0]
L_101_out[7:0]
L_one_line[7..0]
L_101[7..0]
R_101[7..0]
9 BITS
x 1/2
8 BITS
L_121_out[7:0]
L_one_line[7..0]
8 BITS
CLIP
10 BITS
R_one_line[7..0]
R_original[7..0]
8 BITS
Z-1
Z-1
8 bits
9 BITS
x 1/2
R_101[7..0]
R_101_out[7:0]
R_one_line[7..0]
L_101[7..0]
R_101[7..0]
9 BITS
x 1/2
8 BITS
R_121_out[7:0]
R_one_line[7..0]
8 BITS
CLIP
10 BITS
L_one_line[7..0]
If(IN[9]=1) then
OUT[7..0]=0x00;
else
If(IN[8]=1) then
OUT[7..0]=0xFF;
else
OUT[7..0]=IN[7..0];
end if;
end if;

FIG. 10h



NOISE FILTER = OFF

$$\begin{cases} R/Ye = R_{12} \\ G/Mg = g_{12} \\ g/Cy = \dfrac{G_{02}+G_{22}}{2} \\ B/Cy = \dfrac{b_{02}+b_{22}}{2} \end{cases}$$

NOISE FILTER = ON

$$\begin{cases} R/Ye = R_{12} - g_{12} + \dfrac{G_{02}+2g_{12}+G_{22}}{4} \\ G/Mg = \dfrac{G_{02}+2g_{12}+G_{22}}{4} \\ g/Cy = \dfrac{G_{02}+G_{22}}{2} \\ B/Cy = \dfrac{b_{02}+b_{22}}{2} \end{cases}$$

FIG. 10i



FIG. 10j


R/Ye[7..0]
g/G[7..0]
B/Cy[7..0]
G/Mg[7..0]
(R_-1+R_1)/2 - (G_-1+G_1)/2
(B_-1+B_1)/2 - (G_-1+G_1)/2
a=G+Mg-Ye-Cy
9 BITS
12 BITS
CCDMOD
x 2
x 1/2
x -1
11 BITS
CLIP
R/Ye_OUT
B/Cy_OUT
G/Mg_OUT
g/G_OUT
If(IN[10]=1) then
OUT[7..0]=0x00;
else
If(IN[9..8]="00") then
OUT[7..0]=IN[7..0];
else
OUT[7..0]=0xFF;
end if;
end if;

FIG. 10k


ye[7..0]
cy[7..0]
mg[7..0]
Ye−Cy
Ye+Cy
R=Ye−Cy+Mg
B=Mg−Ye+Cy
G=Ye+Cy−Mg
10 BITS
CLIP
CLIP
CLIP
8 BITS
green_ratio[2..0]
x 0, 1, 2, 3, 4
green[7..0]
4−green_ratio[2..0]
x 0, 1, 2, 3, 4
11 BITS
CLIP
8 bits
RGB_mode_sw
RGB_red[7..0]
red_out[7..0]
RGB_mode_sw
RGB_blue[7..0]
blue_out[7..0]
RGB_mode_sw
RGB_green[7..0]
green_out[7..0]
If(IN[9]=1) then
OUT[7..0]=0x00;
else
If(IN[8]=1) then
OUT[7..0]=0xFF;
else
OUT[7..0]=IN[7..0];
end if;
If(IN[10]=1) then
OUT[7..0]=0xFF;
else
OUT[7..0]=IN[9..2];
end if;

FIG. 10l



FIG. 11a



FIG. 11b



FIG. 12a



FIG. 12b



FIG. 13b



FIG. 13a


RAW DATA
10 BITS
SYNC 1402
10 BITS
WHITE BALANCE
1404
8 BITS
CFA INTERP
1406
R
G
B
8 BITS
COMP W/B
COMP W/B
COMP W/B
1408
8 BITS
GAMMA
GAMMA
GAMMA
1410
8 BITS
RGB YCbCr
1412
Y
Cb
Cr
8 BITS
4:2:2 CONV
1414
32 BITS
SDRAM I/F
1416
32 BITS
ARM I/F

FIG. 14


EXTERNAL MEMORY
ARM
SDRAM
SDRAM CONTROLLER
VIDEO
OSD
FIFO
FIFO
CLUT AND WINDOW ATTRIBUTES
BLENDING AND TRANSPARENCY
DISPLAY CONTROL
NTSC/PAL ENCODER

FIG. 15



FIG. 16



FIG. 17



FIG. 18a



FIG. 18b



FIG. 19



FIG. 21



FIG. 20



FIG. 22



FIG. 23a



FIG. 23b



FIG. 23c



FIG. 24



FIG. 25



FIG. 26



FIG. 27


STEP 1
STEP 2
B
ALREADY HAS BLUE
DOES NOT HAVE BLUE
BEING INTERPOLATED

FIG. 28


G
G1
G2
G3
G4
A
5x5 FILTER
B-2
CLIP
INTERPOLATED VALUE
COMPARATOR
B-1
DISCARD THE BIGGEST AND THE SMALLEST
ALREADY HAS GREEN
DOES NOT HAVE GREEN
IS BEING INTERPOLATED

FIG. 29



FIG. 30



FIG. 31



FIG. 32



FIG. 33a



FIG. 33b



FIG. 34

Docket: SC13128A



FIG. 35a



FIG. 35b

SAMSUNG EXHIBIT 2018



FIG. 36a



FIG. 36b

OC 10 07



FIG. 37a



FIG. 37b



FIG. 38



FIG. 39a



FIG. 39b



FIG. 40



FIG. 41a



FIG. 41b



FIG. 42a



FIG. 42b



FIG. 42e

Docket: 3275.2CD



FIG. 42c



FIG. 42d



FIG. 43



FIG. 44



FIG. 45



FIG. 46a



FIG. 46b



FIG. 47



FIG. 49



FIG. 50



FIG. 51a



FIG. 51b


START
$S_n=TP_n=0$, $0 \leq n \leq N$
$n=t=m'=\Delta m=0$
$S_n=1$, SKIP Δm FRAMES
DECODE FRAME m'
Ts=t, n++
COMPUTE TP_n, m', Δm
$n<N_f$?
YES
NO
$n=N_f$, t=0, T=0
END OF SEQUENCE ?
YES
STOP
NO
$Ts=\max\{T, TP_{n+1}\}$
COMPUTE TP_n, m', Δm
$t \geq Ts$?
NO
YES
$S_n=0$, SKIP Δm FRAMES
DECODE FRAME m'
$t<TP_n$?
NO
YES
$T=t$, $\hat{T}_{d+}=DT$, $m=m'$
$S_n=1$, T=t, n++

FIG. 48


LEFT BUFFER
RIGHT BUFFER
FULL
FULL
BUFFER STATUS AFTER INITIALIZATION
Ps
STATUS 0
FULL
FULL
BUFFER STATUS AFTER DECODING A UNIT
Ps
NOT-FULL
FULL
BUFFER STATUS AFTER RE-FILLING BUFFER
Ps
STATUS 1
NOT-FULL
FULL
BUFFER STATUS AFTER DECODING A UNIT
Ps
FULL
NOT-FULL
BUFFER STATUS AFTER RE-FILLING BUFFER
Ps
STATUS 2
FULL
NOT-FULL
BUFFER STATUS AFTER DECODING A UNIT
Ps
NOT-FULL
FULL
BUFFER STATUS AFTER RE-FILLING BUFFER
Ps
STATUS 3

FIG. 52